


TWH-NRH - METRIC SIZE RATCHET HEADS



TWH120NRH-65

- >> Choice of standard metric sizes
 - >> Easily fitted to TWH-N drive units
 - >> Strong steel construction
 - >> Non standard and special design
- ratchet heads can be made to order



The TWH-NRH range of metric hexagon ratchet heads, suitable for use with TWH-N series low profile hydraulic torque wrenches (see pages 75-76), provide exceptional flexibility with across flats (AF) sizes from 24mm to 175mm available as standard. All models feature extremely low profile design combined with a minimum nose radius (R) that enables fitment in very confined limited access places. For even greater versatility a comprehensive range of metric hexagon reducer bushes (see page 81) and square drive conversion kits (see page 79) to suit TWH-NRH metric ratchet heads are also available.



METRIC RATCHET HEAD SELECTION TABLE:

Bolt size	Nut AF size mm	For TWH27N		For TWH54N			For TWH120N			For TWH210N			For TWH430N			
		Model number	R mm	Wt kg	Model number	R mm	Wt kg	Model number	R mm	Wt kg	Model number	R mm	Wt kg	Model number	R mm	Wt kg
16	24	TWH27NRH-24	12.1	1.5												
18	27	TWH27NRH-27	10.4	1.5												
20	30	TWH27NRH-30	10.7	1.6												
22	32	TWH27NRH-32	9.5	1.6												
24	36	TWH27NRH-36	10.1	1.6	TWH54NRH-36	13.8	2.9									
27	41	TWH27NRH-41	10.1	1.6	TWH54NRH-41	10.9	2.8									
30	46	TWH27NRH-46	10.5	1.7	TWH54NRH-46	10.7	2.9									
33	50	TWH27NRH-50	10.4	1.7	TWH54NRH-50	12.1	3.0	TWH120NRH-50	15.2	5.8						
36	55	TWH27NRH-55	10.1	1.8	TWH54NRH-55	12.1	3.1	TWH120NRH-55	15.0	6.1						
39	60	TWH27NRH-60	10.5	1.8	TWH54NRH-60	12.0	3.2	TWH120NRH-60	15.0	6.4						
42	65				TWH54NRH-65	11.7	3.3	TWH120NRH-65	14.9	6.4						
45	70				TWH54NRH-70	11.7	3.4	TWH120NRH-70	14.8	6.5	TWH210NRH-70	18.2	12.1			
48	75				TWH54NRH-75	14.6	3.5	TWH120NRH-75	14.7	6.5	TWH210NRH-75	18.1	12.2			
52	80				TWH54NRH-80	11.7	3.5	TWH120NRH-80	14.7	6.5	TWH210NRH-80	18.1	12.3	TWH430NRH-80	25.6	23.2
56	85							TWH120NRH-85	16.4	7.8	TWH210NRH-85	18.2	12.4	TWH430NRH-85	29.0	24.0
60	90							TWH120NRH-90	16.2	7.9	TWH210NRH-90	18.6	12.4	TWH430NRH-90	31.3	26.0
64	95							TWH120NRH-95	15.9	7.9	TWH210NRH-95	18.6	12.5	TWH430NRH-95	28.5	25.8
68	100							TWH120NRH-100	18.7	8.5	TWH210NRH-100	18.6	12.5	TWH430NRH-100	25.6	25.6
72	105										TWH210NRH-105	18.4	12.9	TWH430NRH-105	28.6	26.5
76	110										TWH210NRH-110	18.3	13.3	TWH430NRH-110	25.7	26.2
80	115										TWH210NRH-115	20.7	13.8	TWH430NRH-115	27.3	26.4
90	130													TWH430NRH-130	25.6	27.3
100	145													TWH430NRH-145	25.4	29.4
110	155													TWH430NRH-155	25.0	30.1
115	165													TWH430NRH-165	25.0	31.0
n/a	175													TWH430NRH-175	27.3	31.8