

SPP - HEAVY DUTY HYDRAULIC PULLERS



Capacities from 83 to 242 tons

Wireless remote controlled operation

Powered driven trolley for easy positioning

The SPP range of heavy duty pullers offers a choice of 18 models with capacities ranging from 83 to 242 tons. The functional and ergonomic design of the heavy duty hydraulic pullers features a movable trolley and the two vertical supports provide stability and safety as well as allow the user to adjust the height to the desired position.

All models include self-centering pulling jaws that can rotate 180° and a wireless remote control that allows for an easier and safer operation. Ideal for use in steel plants, mines, shipyards, petrochemical industries for repair and maintenance applications.



Self-centering puller jaws with anti-slip mechanism



Hydraulic system powered by HEP2 series pump

SPP - HEAVY DUTY HYDRAULIC PULLERS



Self-centering jaw design

Spread up to 48.07 inches

Adjustable height

- >> Hydraulically actuated jaws with adjustable jaw tip angle
- >> Anti-slip mechanism in puller jaws
- >> Easy to manoeuvre with wheel locking feature



Did you know

The SPP pullers incorporate the HEP2 series electric driven pump. For more information on HEP2 series pumps, see page 41.

Model number	Capacity tons	Type of puller	Motor Voltage	Stroke inch	Weight lbs	Dimensions in inches	
						Reach	Spread
Puller with 50Hz motor							
SPP7515	83	2 & 3 jaw	110/115V	6.5	1455	19.31 - 27.58	4.33 - 48.07
SPP7525	83	2 & 3 jaw	220/240V	6.5	1455	19.31 - 27.58	4.33 - 48.07
SPP7545	83	2 & 3 jaw	380/440V	6.5	1455	19.31 - 27.58	4.33 - 48.07
SPP12015	132	2 & 3 jaw	110/115V	6.7	1958	35.46 - 43.34	5.91 - 48.07
SPP12025	132	2 & 3 jaw	220/240V	6.7	1958	35.46 - 43.34	5.91 - 48.07
SPP12045	132	2 & 3 jaw	380/440V	6.7	1958	35.46 - 43.34	5.91 - 48.07
SPP22015	242	2 & 3 jaw	110/115V	6.7	2866	35.46 - 43.34	5.91 - 48.07
SPP22025	242	2 & 3 jaw	220/240V	6.7	2866	35.46 - 43.34	5.91 - 48.07
SPP22045	242	2 & 3 jaw	380/440V	6.7	2866	35.46 - 43.34	5.91 - 48.07
Puller with 60Hz motor							
SPP7516	83	2 & 3 jaw	110/115V	6.5	1455	19.31 - 27.58	4.33 - 48.07
SPP7526	83	2 & 3 jaw	220/240V	6.5	1455	19.31 - 27.58	4.33 - 48.07
SPP7546	83	2 & 3 jaw	380/440V	6.5	1455	19.31 - 27.58	4.33 - 48.07
SPP12016	132	2 & 3 jaw	110/115V	6.7	1958	35.46 - 43.34	5.91 - 48.07
SPP12026	132	2 & 3 jaw	220/240V	6.7	1958	35.46 - 43.34	5.91 - 48.07
SPP12046	132	2 & 3 jaw	380/440V	6.7	1958	35.46 - 43.34	5.91 - 48.07
SPP22016	242	2 & 3 jaw	110/115V	6.7	2866	35.46 - 43.34	5.91 - 48.07
SPP22026	242	2 & 3 jaw	220/240V	6.7	2866	35.46 - 43.34	5.91 - 48.07
SPP22046	242	2 & 3 jaw	380/440V	6.7	2866	35.46 - 43.34	5.91 - 48.07